



Southwire™

ARANDELAS REDUCTORAS DE SALIDA

CARACTERÍSTICAS

- Usar en pares

APLICACIÓN

- Se utiliza para reducir el tamaño de agujeros de knockout.

MATERIAL ESTÁNDAR

- Acero galvanizado por inmersión en caliente

CERTIFICACIONES

- Listado UL



902

NÚMERO DE PARTE	REDUCE AGUJEROS KO DE	MAESTRO TØ	CANTIDAD
900	3/4"	1/2"	100
901	1"	1/2"	100
902	1"	3/4"	100
903	1-1/4"	1/2"	50
904TZ	1-1/4"	3/4"	50
905	1-1/4"	1"	50
906	1-1/2"	1/2"	50
907	1-1/2"	3/4"	50
908	1-1/2"	1"	50
909	1-1/2"	1-1/4"	50
910	2"	1/2"	50
911	2"	3/4"	50
912	2"	1"	50
913	2"	1-1/4"	50
914	2"	1-1/2"	50
915	2-1/2"	1/2"	50
916	2-1/2"	3/4"	50
917	2-1/2"	1"	50
918	2-1/2"	1-1/4"	50
919	2-1/2"	1-1/2"	50
920	2-1/2"	2"	50
921TZ	3"	1/2"	25
922TZ	3"	3/4"	25

NÚMERO DE PARTE	REDUCE AGUJEROS KO DE	MAESTRO TØ	CANTIDAD
923	3"	1"	25
924	3"	1-1/4"	25
925TZ	3"	1-1/2"	25
926TZ	3"	2"	25
927	3"	2-1/2"	25
928TZ	3 1/2"	1/2"	10
929	3-1/2"	3/4"	25
930	3-1/2"	1"	25
931	3-1/2"	1-1/4"	25
932TZ	3-1/2"	1-1/2"	25
933	3-1/2"	2"	25
934	3-1/2"	2-1/2"	25
935	3-1/2"	3"	25
936TZ	4"	1/2"	10
937	4"	3/4"	10
938	4"	1"	10
939	4"	1-1/4"	10
940	4"	1-1/2"	10
941	4"	2"	10
942	4"	2-1/2"	10
943	4"	3"	10
944	4"	3-1/2"	10

Rev. 0, 05/23



1-855-798-6657 | SOUTHWIRE.COM

©2023 Southwire Company, LLC. Todos los derechos reservados.

*Marca Registrada & ™ Marca de Southwire Company, LLC.