



Southwire™

ARE DOUBLE GANG

ANILLOS PARA DISPOSITIVOS

CARACTERÍSTICAS

- Las ranuras anguladas en las tapas compensan hasta 12° de desalineación de caja en miembros de marco vertical

APLICACIONES

- Los anillos para dos dispositivos cuadrados de 4-11/16" se utilizan con cajas cuadradas de 4-11/16" para montar interruptores, receptáculos y dispositivos

MATERIAL ESTÁNDAR

- Acero galvanizado por inmersión en caliente

CERTIFICACIONES

- Listado UL, cULus



72C20A



NÚMERO DE PARTE	DESCRIPCIÓN	ELEVADO	CÚBICO PULGADAS (CM³)	MAESTRO CANTIDAD
72C20A	PARA ACABADO DE PLACA SECA	PLANO	---	50
72C20		1/4"	3.0 (49.2)	50
72C17		1/2"	5.5 (90.3)	25
72C18-5/8		5/8"	7.3 (119.6)	25
72C18		3/4"	8.8 (144.2)	25
72C19		1"	12.0 (196.6)	25
72C21		1-1/4"	15.0 (245.8)	25
72C24		1-1/2"	15.5 (254.0)	25
72C25		2"	20.5 (335.9)	25

Rev. 1, 3/24



1-855-798-6657 | SOUTHWIRE.COM

©2024 Southwire Company, LLC. Todos los derechos reservados.

*Marca Registrada & ™ Marca de Southwire Company, LLC.



Southwire™

ARE DOUBLE GANG

ANILLOS PARA DISPOSITIVOS



72C20



72C17



72C18-5/8



72C18



72C19



72C21



72C24



72C25

Rev. 1, 3/24

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2024 Southwire Company, LLC. Todos los derechos reservados.

*Marca Registrada & ™ Marca de Southwire Company, LLC.